



Roller door profile 1.1440

for small- and medium-size
roller shutter doors.

ferdinand
braselmann.de

Vielfalt mit Profil

Roller door profile 1.1440



1.1440



1.144 L

The profile 1.1440 is an uncomplicated single wall roller door profile, designed for use in small- to medium-size roller doors.

The 1.144L version – as a perforated plate profile – is not only used wherever air permeability is required, but is also outstandingly suited to the protection of objects such as shop windows in which transparency and optical relaxation are also desired in addition to good protection.

• material thickness [mm]

	0,80	1,00	1,25	1,50
steel, galvanized	•	•P	•	•
steel, powder colour coated	•	•P	•	•
aluminium, bright		•	•P	•
aluminium, powder colour coated		•	•P	•
aluminium, plastic film coated		•	•	
aluminium, anodized 3μ		•	•	•
aluminium, anodized 20μ		•	•	•
stainless steel		•P		

P= perforated plate available

• technical details

slats on 1 m height: 14,5
thickness of slats: ~ 19 mm

• weight (at 1,00 mm)

aluminium: ~ 0,34 kg/m (4,9 kg/m²)
steel: ~ 0,98 kg/m (14,2 kg/m²)

• maximum door width [mm] (wind class 2, without storm hooks)

	0,80	1,00	1,25	1,5
steel, stainless steel	6.600	7.200	7.700	8.200
aluminium	4.900	5.300	5.700	6.000

• calculated bale diameter [mm]

opening height	tube diameter [mm]								
	89	108	133	159	169	194	219	267	324
2 m	250	260	280	280	290	310	330	370	400
2,5 m	270	270	280	300	310	340	350	390	430
3 m	290	300	310	330	330	340	360	400	430
3,5 m	300	310	330	340	350	370	370	420	450
4 m	330	330	340	370	370	370	390	420	470
4,50 m	330	340	370	370	380	400	400	450	470
5 m		360	370	390	390	400	420	450	490
6 m			400	420	420	440	460	480	500
7 m						460	460	500	540