



Refrigerated Dock Seal Refrigerated Dock Seal with Adjustable Head

ABFR
ABFM

Perfect, long-lasting insulation for temperature controlled facilities.

TECHNICAL DESCRIPTION

Inkema's ABFR / ABFM Refrigerated Dock Seals are made from high recovery index foam covered with a PVC-coated polyester fabric canvas.

The canvas cover's welded edges make **Inkema** refrigerated dock shelters more resistant to the friction caused by contact between the lorry and the shelter during docking.

Refrigerated seals are designed to always ensure the best insulation during vehicle loading and unloading manoeuvres, and to absorb possible impacts on the building.



REFRIGERATED SHELTER - ABFR



- 1 0.5mm thick PVC canvas covers.
- 2 Galvanised tube perimeter structure (movable ABFM).
- 3 Vertical reflective bands.
- 4 Welded reinforcements/edges for increased durability.
- 5 Galvanised steel cover (movable ABFM).
- 6 Adjustable and movable roof (movable ABFM).
- 7 Fixed roof (ABFR).

CUSHION MATERIAL

The set consists of two side cushions filled with foam rubber, and a top cushion made of foam rubber, which forms the roof. The side cushion blocks are PVC covered and screen-printed with stripes, providing visual support for manoeuvring lorries.

These cushions are covered with 0.5mm black PVC canvas, so they are **very resistant to the friction** caused by contact with lorry trailers. They **fit perfectly** to the lorry's trailer, and are also highly resistant to adverse weather conditions, **making them even more durable.**

REFRIGERATED SHELTER WITH ADJUSTABLE ROOF - ABFM



The ABFM shelter is very resilient and resistant to the friction.



It adjusts perfectly to the height of even the smallest vehicles.

Shelters	ABFR	ABFM (movable head)
Width	From 1400 mm. up to 2600 mm.*	From 1400 mm. up to 2600 mm.*
Height	From 1700 mm. up to 2900 mm.*	From 2500 mm. up to 2900 mm.*
Range of movement of top foam	---	1000 mm.

* for other specific measurements, consult Customer Service.

Dock Shelters



The range of movement of the ABFM's upper canvas is 1000mm.

PREPARED TO WITHSTAND CONSTANT FRICTION

Refrigerated Dock Seals ABFR / ABFM:

When a vehicle begins to approach the loading dock in order to unload, it rests against the **Refrigerating Dock Seal**, compressing it, because of its flexible foam composition.

As a result, the dock shelter lines up perfectly against the vehicle's trailer, preventing air and elements from passing from the outside to the inside.

In the case of the **ABFM seal**, the movable head panel adjusts to match different vehicle heights. The range of movement of the upper canvas is 1000mm.

SAFETY

All **Refrigerated Dock Seals** are equipped with vertical reflective bands that make it easier for drivers to manoeuvre, and avoid collisions that could damage the facility and the vehicle.



The ABFR is manufactured using only high quality materials.



Refrigerated dock shelters are installed directly on the façade.

OPTIONS

The **Refrigerated Dock Seals - ABFR/ABFM** offer a variety of options that allow its customers to customise the shelter according to their needs and requirements.

For example, the possibility of adding wheel guides **to the loading dock**. Ask the Customer Service for more information.



Wheel guides make it easier for vehicles to enter the loading docks, and they protect them from possible knocks.

Dock Shelters

www.inkema.com

C/ Galileo, 2 – Naves 4 - 12 – Apartado de correos 132 – 08150 Pareds del Vallés – Barcelona – (Spain)
For further information please contact us by phone +34 93 544 47 08 or by email: export@inkema.com